

Technical data

# HC 130i VIO



**Compactors Series HC**  
Compactor with VIO drum

**H254**

## HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

**TECHNICAL DATA HC 130i VIO (H254)**

**Weights**

Operating weight with cab	kg lbs	13210 29,128
Operating weight with ROPS	kg lbs	13090 28,863
Empty weight without cab, without ROPS	kg lbs	12235 26,978
Max. operating weight	kg lbs	17650 38,918
Axle load, front/rear	kg lbs	7600/5610 16,758/12,370
Axle load for max. operating weight, front/rear	kg lbs	8330/9320 18,368/20,551
Static linear load, front	kg/cm lbs/in	35,51 198.8
French classification, value/class		48,12/VM3
Wheel load per tire, rear	kg lbs	2805 6,185

**Machine dimensions**

Total length	mm in	6117 240.8
Total height with cab	mm in	3054 120.2
Total height with ROPS	mm in	3054 120.2
Height loading, min.	mm in	3054 120.2
Center distance	mm in	3266 128.6
Total width with cab	mm in	2474 97.4
Maximum working width	mm in	2140 84.3
Ground clearance, center	mm in	461 18.1
Curb clearance, left/right	mm in	477/477 18.8/18.8
Turning radius, inside	mm in	4131 162.6
Slope angle, front/rear	°	34,2/23,7

**Drum dimensions**

Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1504 59.2
Drum thickness, front	mm in	20 0.8
Drum type, front		Smooth

**Tire dimensions**

Tire size, rear		AW 23.1-26 12 PR
Width over tires, rear	mm in	2122 83.5
Number of tires, rear		2

**Diesel engine**

Model		JDPS 4045PSS
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		119,6/162,6/2000
Power SAE J1349, kW/HP/rpm		119,6/160,4/2000
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

**Travel drive**

Speed, infinitely variable	km/h mph	0 - 12,1 0.0 - 7.5
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	52/58

**Vibration**

Vibration frequency	Hz vpm	33 1,980
Amplitude, vibr.	mm in	1,95 .077
Centrifugal force, vibr.	kN lbs	280 63,000

**Oscillation**

Oscillation force	kN lbs	230,2 51,795
Oscillation frequency	Hz vpm	30 1,800
Tangential amplitude, oscillation	mm in	1,62 .064

**Steering**

Swing angle +/-	°	max. 12
Steering, type		Articulated steering

**Tank capacity/filling capacity**

Fuel tank, capacity	L Gal	280 74.0
AdBlue/SCR reducing agent tank, capacity	L Gal	32 8.5

**Sound level**

Sound power level L(WA), guaranteed	db(A)	108
Sound power level L(WA), representative measurement	db(A)	106

**EQUIPMENT**

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system

**OPTIONAL EQUIPMENT**