

Technical data

HX 70i VT-S



Tandem rollers Series HX

Tandem roller with vibrating roller drum and set of wheels

H297

HIGHLIGHTS

- > High compaction performance due to optimal setting of the compaction parameters
- > Intelligent water sprinkler system
- > Operating concept Easy Drive
- > Innovative cabin concept for optimal visibility and high comfort
- > Digital ready

TECHNICAL DATA HX 70i VT-S (H297)

Weights

Operating weight with cab	kg lbs	7750 17,089
Empty weight without cab, without ROPS	kg lbs	6725 14,829
Maximum operating weight	kg lbs	10340 22,800
Axle load, front/rear	kg lbs	3990/3760 8,798/8,291
Axle load at maximum operating weight, front/rear	kg lbs	3560/6780 7,850/14,950
Static linear load, front	kg/cm lbs/in	26,60 149.0
French classification, value/class		20,8/VX1
Wheel load per tire, rear	kg lbs	940 2,073

Machine dimensions

Total length	mm in	4177 164.4
Total height with cab	mm in	2960 116.5
Height loading, min.	mm in	2170 85.4
Center distance	mm in	3000 118.1
Total width with cab	mm in	1680 66.1
Maximum working width	mm in	2770 109.1
Ground clearance, center	mm in	280 11.0
Curb clearance, left/right	mm in	610/610 24.0/24.0
Turning radius, inside	mm in	2800 110.2

Drum dimensions

Drum width, front	mm in	1500 59.1
Drum diameter, front	mm in	1140 44.9
Drum thickness, front	mm in	17 0.7
Drum type, front		Smooth/split
Track offset, left/right	mm in	1270 50.0

Tire dimensions

Tire size, rear		11.00-20
Width over tires, rear	mm in	1490 58.7
Number of tires, rear		4

Diesel engine

Manufacturer		Kubota
Model		V3307-CR-TE5AB

Diesel engine

Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		54,6/74,3/2200
Power SAE J1349, kW/HP/rpm		55,4/74,2/2200
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF

Travel drive

Speed, infinitely variable	km/h mph	0-11,1 0.0-6.9
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	39/43

Vibration

Vibration frequency, front, I/II	Hz vpm	42/50 2,520/3,000
Amplitude, front, I/II	mm in	0,58/0,40 .023/.016
Centrifugal force, front, I/II	kN lbs	63,23/62,57 14,227/14,078

Steering

Pendulum angle +/-	°	4
Steering, type		All-wheel, analogue

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L Gal	148 39.1
Water tank, capacity	L Gal	740 195.5

Sound level

Sound power level L(WA), guaranteed	db(A)	104
Sound power level L(WA), representative measurement	db(A)	103

EQUIPMENT

Scrapers foldable | Easy Drive operating concept | Pressure water sprinkling system | ECO mode | Frequency control | Speed preselect | Track offset, hydraulic | Automatic vibration system | Water filter system (3-fold) | Central water outlet | Camera system, front and rear | Working spotlights

OPTIONAL EQUIPMENT

ROPS cab with split doors | Heating and air-conditioning system | Tachograph | Bluetooth interface for Smart Doc | Smart Compact | Weather station | Edge pressing and cutting equipment | Chip spreader | Thermal aprons | HAMM Compaction Meter (HCM) | Speedometer | Automatic engine stop | HAMM Temperature Meter (HTM) | Back-up alarm | JDLINK | Drum edge lighting | Drum lighting | Coming Home function